



NEO connect PLUS is the biometric terminal for Time & Attendance and Access Control that combines a sleek and fashionable design with ease to use, functionality and reliable performance.

The solution has been developed with cutting edge technology to guarantee an accurate process.

NEO connect is the perfect choice for offices, small and medium size businesses which require an accurate and affordable biometric system to automate their T&A and/or access control process.

- Sleek and elegant design, suitable for office environments
- USA TI 300 MHZ high speed processor
- Super long life keypad
- Free maintenance fingerprint sensor
- TCP/IP and USB communications
- USB port for easy data transfer to a USB Flash disk (pen drive)
- Relay output to control the door open
- Identification method: Fingerprint, Fingerprint + ID, ID + Password
- Fingerprint capacity: 2,000
- Record capacity: 50,000
- Identification speed: < 0.5 second



T&A



Identification



USB



Main Features

- Sleek and elegant design, suitable for office environments
- USA TI 300 MHZ high speed processor
- BioNANO™ Core Fingerprint Algorithm of high speed and stability. It heals broken fingerprint lines; intelligent fingerprint templates update. New version of the algorithm with improved performance on wet and dry fingerprints. Support identification from different angles.
- New generation fully sealed, waterproof, dustproof and free maintenance fingerprint sensor
- User name display and human voice prompt
- Relay output to control the door open
- TCP/IP and USB communications
- USB port for easy data transfer to a USB Flash disk (pen drive)
- Identification method: Fingerprint, ID + Fingerprint, ID + Password
- Fingerprint capacity: 2,000
- Record capacity: 50,000
- Identification speed: < 0.5 second
- Size: 200 mm(w) x 140mm (h) x 38mm (d)
- Wall mounted



Neo connect PLUS builds-up BioNano® Technology, new generation identification fingerprint algorithm with high speed and stability. BioNano® heals broken fingerprint lines and updates fingerprint templates (intelligent function).

Specifications

Sensor	Optical	Working Current	1A
LCD Display (Res)	Blue 128 x 64	Sleeping Current	0.3A
Identification Method	FP, ID+FP, ID+Password	ESD Tolerance	>15,000V
Identification Time	< 0.5 Sec.	Power	DC 5V
Register Method	Fingerprint, password	Temperature / Humidity	-10 - 60°C / 20 - 80%
Fingerprint Capacity	2,000	Material	ABS Plastic
Record Capacity	50,000	Dimensions	200 x 140 x 38 mm (W, H, D)
FRR	0.001%	Color	Black
FAR	0.00001%	Scan Area	22 x 18 mm
Standard Port	USB and TCP/IP - USB port for easy data transfer to Pen Drive**		

About EasyWay Biometrics

EasyWay Biometrics is the new brand of innovative fingerprint solutions for Time & Attendance and Access Control needs. Every EasyWay terminal has been designed with international quality standards, combining fashionable design with outstanding performance

EasyWay uses the latest technology to create products that provide a functional solution for customers who need low cost T&A and Access Control solutions.

NEOCP-111208-1

www.easywaybiometrics.com

info@easywaybiometrics.com